


ACE-828A



Specifications

| Input Type | 90 ~ 130 VAC, 180 ~ 260 VAC Auto Range | | | | | |
|------------------|---|---------------|-----------------|------|------|-------|
| Output Voltage | +3.3V | +5V | +12V | -5V | -12V | +5Vsb |
| | 8A | 25A (2A min.) | 10A (0.1A min.) | 0.5A | 0.5A | 0.72A |
| Efficiency | 65% | | | | | |
| Temperature | Operating: -20°C ~ 70°C (40°C ~ 70°C derating curve) Storage: -40°C ~ 75°C | | | | | |
| MTBF (hrs) | 110,000 | | | | | |
| Output Connector | 1 x 20-pin ATX, 5 x HDD/CDROM, 2 x FDD | | | | | |

Ordering Information

| Part No. | Description |
|-------------|----------------------------------|
| ACE-828A-RS | 280W AC-DC PS/2 ATX Power Supply |

ACE-828M



Medical



Specifications

| Input Type | 90 ~ 130 VAC, 180 ~ 260 VAC Auto Range | | | | | |
|------------------|---|---------------|-----------------|------|------|-------|
| Output Voltage | +3.3V | +5V | +12V | -5V | -12V | +5Vsb |
| | 8A | 25A (2A min.) | 10A (0.1A min.) | 0.5A | 0.5A | 0.72A |
| Efficiency | 65% | | | | | |
| Temperature | Operating: -20°C ~ 70°C (40°C ~ 70°C derating curve) Storage: -40°C ~ 75°C | | | | | |
| MTBF (hrs) | 170,000 | | | | | |
| Output Connector | 1 x 20-pin ATX, 5 x HDD/CDROM, 2 x FDD | | | | | |

Ordering Information

| Part No. | Description |
|-------------|--|
| ACE-828M-RS | 280W AC-DC PS/2 ATX Power Supply, meets medical standard |

PS/2 AC Input AT Type

ACE-932A



Specifications

| Input Type | 85 ~ 130 VAC, 180 ~ 265 VAC Auto Range | | | | | |
|------------------|---|----------------|-----------------|-------|-------|--------|
| Output Voltage | +3.3 V | +5 V | +12 V | -5 V | -12 V | +5 Vsb |
| | | 33A (3 A min.) | 8A (0.2 A min.) | 0.5 A | 3 A | |
| Efficiency | 68% | | | | | |
| Temperature | Operating: 0°C ~ 50°C (50°C ~ 70°C derating curve) Storage: -40°C ~ 75°C | | | | | |
| MTBF (hrs) | 120,000 | | | | | |
| Output Connector | 1 x P8+P9, 1 x Extra +5V (P10), 4 x HDD/CDROM, 2 x FDD | | | | | |

Ordering Information

| Part No. | Description |
|-------------|----------------------------------|
| ACE-932A-RS | 300 W AC-DC PS/2 AT Power Supply |

ACE-935AL



Specifications

| Input Type | 85 ~ 140 VAC, 170 ~ 270 VAC Auto Range | | | | | |
|------------------|--|----------------|-----------------|-------|-------|--------|
| Output Voltage | +3.3 V | +5 V | +12 V | -5 V | -12 V | +5 Vsb |
| | | 40 A (3A min.) | 8 A (0.1A min.) | 0.3 A | 0.7 A | |
| Efficiency | 68% | | | | | |
| Temperature | 0°C ~ 50°C (Operating), -40°C ~ 75°C (Storage) | | | | | |
| MTBF (hrs) | 100,000 | | | | | |
| Output Connector | 1 x P8+P9, 1 x Extra +5V (P10), 5 x HDD/CDROM, 2 x FDD | | | | | |

Ordering Information

| Part No. | Description |
|--------------|--|
| ACE-935AL-RS | 300 W AC-DC PS/2 AT Power Supply, AC select switch |