

ICEFIRE-ET

Enterprise Tablet PC

- 10.4" TFT 350 cd/m² XGA LCD with Multi-resistive touch
- Intel® Atom™ D525 dual core platform
- Powered by Windows® Embedded Standard 7 P
- 3M pixels camera with LED flash
- Bluetooth, Wi-Fi, Ethernet LAN
- Dual hot swappable batteries
- Optional Docking Station / Smart card reader



Application




Enterprise Mobility

Using technology to quickly move products helps save you time, increasing productivity. The right technology enables the flow of information between handheld devices used by your workers and your core business systems. ICEFIRE –ET mobile computing, wireless local area networks (WLANs) and management software to speed the transfer of data and optimize your working mobility in logistic and warehousing environment

Home Automation and Education

Instead of rugged design makes tablet PC heavy and suburb the stylish and ergonomic design makes ICEFIRE-ET perfect for home automation control system and E-education device.



Logistic and Warehouse

Enhancing on-duty people work force and mobility, tablet PC brings you more efficiency than you can imagine. Keep all the data and information in ICEFIRE-ET and transmit via wireless communication can provide your real-time responds without any lost.



Specifications

| Model | | ICEFIRE-ET |
|--------------------------|---------------------------------|---|
| Display | LCD Size | 10.4" TFT LCD |
| | Brightness (cd/m ²) | 350 cd/m ² |
| | Max Resolution | 1024 x 768 pixels XGA |
| | Viewing Angle | 88/88/88/88 Deg. |
| | Touch Screen | Resistive Support Multi-touch and Gesture |
| System | CPU | Intel® Atom™ D525 1.8GHz |
| | Chipset | Intel® ICH8M |
| | Operation System | Microsoft® Windows® Embedded Standard 7 P |
| | Memory | 2GB DDR3 SDRAM 1333MHz |
| Communication | Storage | 1.8" SSD, SATA |
| | Wireless LAN | Wi-Fi® 802.11a/b/g/n |
| Data Collection | Bluetooth | Bluetooth® V2.1+ EDR (Class II) |
| | Camera | 3M pixel and LED Light |
| Indicator & Buttons | LED Indicator | Power/ Wifi/Bluetooth/ Battery Status LED |
| | Keys | 5-way Navigation key Camera/Wi-Fi/Bluetooth/SAS/Function Key |
| I/O Interface | USB | 1 x USB 2.0 FULL SPEED |
| | LAN | 1 x 10/100M LAN |
| | Audio | 1 x 2W Speaker |
| | | 1 x Mic in |
| Power | Power Adapter | 12V@5A@60W |
| | Docking Power Adapter | 19V@4.74A@90W |
| | Battery | 11.1V 1880mAh Li-ion Battery |
| Environment | Operating Temperature | 0°C to +40°C |
| | Storage Temperature | -10°C to +60°C |
| | Humidity | 5%~95% non-condensing |
| | Drop Survival | 1.0 M |
| | Environmental Protection | Front Panel IP64 compliant |
| | Certification | UL/CE/FCC, |
| | | |
| Physical Characteristics | Dimensions (LxWxH) (mm) | 270 x 265 x 29 |
| | Weight | 1,788g |

Ordering Information

With SSD&OS

| Part No. | Description |
|----------------------------|--|
| ICEFIRE-T10A-ET/2G-32S-R10 | 10.4" TFT-LCD 350 cd/m ² XGA Industrial Mobile Clinical Assistant with Dual-core Intel® Atom™ D525 1.8GHz CPU Integrate Resistive Touch, 2GB DDR3 RAM, 802.11 a/b/g/n Wireless, Bluetooth, 3M Pixels Camera, 32G SSD, WS7P RoHs |

Packing List

| Item | Part No. |
|---|-------------------------|
| Stylus | XTR104-0002-RS |
| Battery Pack-B | 31603-000020-RS |
| Non-Medical-grade Power Adapter (12V/60W) | 63000-FSP060DBAB1553-RS |
| User's Manual CD ROM | 7B000-000552-RS |

Dimensions (Unit: mm)

