






## Drive Cage *Standard 3.5" devices 5.25" Drive Bay Solutions*

Following the traditional industrial system needs for stability, durability and toughness for storage drive operating condition, IEI provides various kinds of standard 3.5" devices 5.25" removable drive bay and modules for each different demands.

	SATA / IDE / SSD Solution		SATA / IDE / SSD	SATA Solution	
					
<b>Model Name</b>	<b>XWC-410030507220-RS</b>	<b>XWC-410030507230-RS</b>	<b>AS-25D2-R10</b>	<b>RD-03A-RS-R10</b>	<b>RHD-302SATA-RS-R11</b>
<b>Dimensions (L x W x H) (mm)</b>	150 x 146 x 42	150 x 146 x 42	143 x 106 x 26	190 x 148 x 42	220 x 148 X 85.8
<b>Material</b>	Aluminum	Aluminum	Plastic body with stainless steel 2.5" HDD bracket	Aluminum alloy	Aluminum alloy
<b>Interface</b>	SATA / IDE / SSD	SATA / IDE / SSD	SATA / IDE / SSD	SATA	SATA
<b>Data Transfer Rate</b>			No	up to 300MB/Sec	up to 300MB/Sec
<b>Drive Bay Space</b>	One 5.25" Device Bay	One 5.25" Device Bay	One 3.5" Device Bay	One 5.25" Device Bay	2 x 5.25" drive bay for 3 x 3.5" HDD
<b>HDD Type</b>	Internal 3.5" device bay	Internal 3.5" device bay	2.5" IDE / SATA SSD x 2	3.5" SATA	3.5" SATA
<b>Cooling Fan</b>			Open air design for maximum air flow and cooling	4010 ball bearing	8020 ball bearing (Removable)
<b>Hot Swap</b>	No	No	No	Yes	Yes
<b>Keylock</b>	No	No	No	Yes	No
<b>Signal Out</b>	No	No	No	Power on signal out (high) HDD access signal out (high)	3 x HDD power signal out (+5V, GND) 1 x Temperature overheat signal out (5V, GND) 1 x Fan fail signal out (5V, GND) 3 x HDD access signal out (+5V, GND) 1 x Reset signal out (High, GND)
<b>Color</b>	Black	White	Black	White / Black	Black bezel and silver housing
<b>G.W.</b>	0.2kg	0.2kg	0.125kg	0.3kg	1.0kg

	SATA Solution				
					
<b>Model Name</b>	<b>RHD-102SATA-R10</b>	<b>RHD-102DW-R10</b>	<b>RHD-101SATA-R10</b>	<b>RHD-104SATA-R10</b>	<b>RHF-21-SATA-R10</b>
<b>Dimensions (L x W x H) (mm)</b>	101.2 x 25.4 x 133	170 x 146 x 41	135 x 101.6 x 25.6	170 x 146 x 41.3	151.5 x 102 x 25.7
<b>Material</b>	Metal	Aluminum & SECC	SECC	SECC	SECC
<b>Interface</b>	7-pin SATA x 2	SAS / SATA	7-pin SATA x 2	7-pin SATA x 4	SATA
<b>Data Transfer Rate</b>	up to 6Gb/Sec	up to 6Gb/Sec	Up to 600 MB/sec	Up to 600 MB/sec	No
<b>Drive Bay Space</b>	One 3.5" Device Bay	One 5.25" Device Bay	One 3.5" Device Bay	One 5.25" Device Bay	Internal 3.5" device bay
<b>HDD Type</b>	2.5" SAS or SATA I / II / III 2 x HDD/SSD	2.5" SAS 2.0 or SATA I / II / III 2 x HDD/SSD	2.5" SAS or SATA I / II / III 1 x HDD/SSD	2.5" SAS or SATA I / II / III 4 x HDD/SSD	2.5" SATA HDD
<b>Cooling Fan</b>	No	No	Metal heat dispersion	2 x 40 mm rear outtake fan w/ aluminum heat dissipation	No
<b>Hot Swap</b>	Yes	Yes	Yes	Yes	Yes
<b>Keylock</b>	Yes	2 x Section key lock	2 x segment key lock	No	Yes
<b>Signal Out</b>	2 x HDD power signal out 2 x HDD access signal out	1 x Silm Type ODD 2 x HDD power signal out 2 x HDD access signal out	1 x HDD power signal out 1 x HDD access signal out	4 x HDD power signal out 4 x HDD access signal out	1 x Female connector 1 x SATA LED signal connector 1 x Power LED connector 1 x Key on/off connector 1 x Power/SATA LED connector 1 x Male connector
<b>Color</b>	Black	Black	Black	Black	Black
<b>G.W.</b>	0.375kg	0.8kg	0.483kg	0.95kg	0.3kg